


POWEROPE - COMPACTED STRANDS WIRE ROPE

 6X19 SEALE	Nominal diameter	Weight	Calculated breaking load		Minimum breaking load	
			1960 N/mm ²	(200 kg/mm ²)	1960 N/mm ²	(200 kg/mm ²)
			mm	kg/m	kN	(t)
	8	28.2	65.0	6.63	54.1	5.52
	9	36.9	85.1	8.68	68.3	6.97
	10	44.9	103.5	10.55	84.3	8.60
	11	54.6	126.0	12.85	103.2	10.53
	12	64.3	148.3	15.12	123.0	12.55
	13	75.8	174.7	17.82	144.9	14.79
	14	87.6	201.9	20.59	167.5	17.09
	15	100.2	230.9	23.55	192.2	19.61
	16	112.9	260.3	26.54	215.6	22.00
	17	128.9	279.3	30.32	246.4	25.15
	18	141.7	326.7	33.31	270.6	27.61
	19	160.5	370.0	37.73	306.7	31.30
	20	177.1	408.4	41.64	338.6	34.55
	21	196.7	453.5	46.24	375.1	38.27
	22	218.2	503.1	51.30	417.2	42.57
	23	235.2	542.4	55.31	449.5	45.87
	24	257.4	593.5	60.52	490.9	50.09
	25	276.1	636.6	64.91	527.1	53.79
	26	302.2	696.8	71.05	577.0	58.88
	27	322.3	743.2	75.79	616.7	62.93
	28	344.9	795.2	81.09	659.0	67.24
	29	371.1	855.8	87.27	711.5	72.61
	30	395.7	912.5	93.05	757.3	77.28
	32	449.1	1035.6	105.60	860.5	87.81
	34	507.9	1171.3	119.43	969.6	98.95
	35	567.8	1309.4	133.52	1085.0	110.72
	38	634.0	1461.8	149.06	1210.2	123.49
	40	705.5	1626.8	165.89	1348.5	137.60

1Kg=9.80665 N (Newton)